

TECHNICAL DATA SHEET



0090 212 447 0 446

CP 55-724 GREEN MASTERBATCH

AREAS OF APPLICATION:

- Film
- Injection
- Blow Molding
- Extrusion

CHEMICAL SPECIFICATION:

- | | |
|----------------------|-----------------|
| Color Index | Color Index DIN |
| Color provision | 55949 |
| Carrier Raw material | LDPE (MFI=20) |

TECHNICAL SPECIFICATION:

- | | |
|----------------------------------|---------------------------------------|
| Light Fastness | 4 (DIN 54004) |
| Heat Resistance | 230°C (DIN 53772) |
| Compatibility with food industry | Compatible |
| Usage range | 0,5-1% based on product specification |

GENERAL SPECIFICATION:

- | | |
|---|-------------------------|
| Areas of application | PE, PP, PS |
| Appearance | Granule |
| Package type | Laminated, PP Jute bags |
| Package size | 25 Kg. |
| Granule Homogeneity | Approved |
| Batch Homogeneity | Approved |
| Granule Size | 3 ± 0.5mm |
| Appropriate to general masterbatch specifications | |

SHELF LIFE:

The shelf life of the product is one year in room temperature and its unopened original container.

The information stated above is the company's self experiment and gathered mainly based on the data derived from raw material suppliers and informed as a guide to users based on typical test values. As a matter of fact, it might not be regarded as standard data.

It is highly recommended to make a trial operation based on the specific application of the product before the main production.



Headquarter :
Maslak Mah. Büyükdere Caddesi Maslak Meydan Sokak Veko Giz Plaza
No:21 K.14 Sarıyer / İstanbul/ TURKEY

E-Mail: info@tuaykimya.com Web: www.tuaykimya.com

